

SHARP

NU Series (60 cells)
245 W | 240 W | 235 W

Monocrystalline silicon photovoltaic modules




Say yes to solar power! Because it protects the climate.

Innovations from a photovoltaic pioneer

As a solar specialist with 50 years' experience in photovoltaics (PV), Sharp makes significant contributions to ground-breaking progress in solar technology.

Sharp photovoltaic modules in the NU series are designed for applications with high power requirements. These quality monocrystalline modules produce a continuous, reliable yield, even under demanding operational conditions.

All Sharp NU series modules offer system integration which is optimal both technically and economically, and are suitable for installations in on and off-grid PV systems.



Brief details for the installer

- 156.5 mm × 156.5 mm dark blue monocrystalline solar cells
- 60 cells in series
- 2,400 N/m² mechanical load-bearing capacity (245 kg/m²)
- 1,000 V DC maximum system voltage
- IEC/EN 61215, IEC/EN 61730, Application class A
- Class II (VDE: 40021391)

Product features

- High-performance photovoltaic modules made of dark blue monocrystalline (156.5 mm)² silicon solar cells with module efficiencies of up to 14.9%.
- Anti-reflex coating to increase light absorption (for NU-E245J5 and NU-E240J5).
- Bypass diodes which minimise the loss in output when shading occurs.
- Textured cell surface for particularly high electricity yields.
- BSF structure (Back Surface Field) to optimise cell efficiency.
- Use of tempered white glass, EVA plastic, and weather protection film, as well as a silver anodised aluminium frame with drainage holes for long-term use.
- Output: connection cable with waterproof plug connector.

Quality from Sharp

Benchmarks are set by the quality standards of Sharp Solar. Continual checks guarantee a consistently high level of quality. Every module undergoes visual, mechanical, and electrical inspection. This is recognisable by means of the original Sharp label, the serial number, and the Sharp guarantee:

- 5 year product guarantee
- 10 year performance guarantee for a power output of 90%
- 25 year performance guarantee for a power output of 80%

The detailed guarantee conditions and additional information can be found at www.sharp.eu.

Mechanical data

Cell	Monocrystalline (156.5 mm) ² silicon solar cell
Quantity and wiring of cells	60 in series
Dimensions	1,652 × 994 × 46 mm (1.64 m ²)
Weight	19 kg
Connection type	Cable with plug connector (MC-3)

Limit values


Operating temperature (cell)	- 40 to +90	°C
Storage temperature		
Storage air humidity (relative)	up to 90	%
Maximum system voltage	1,000	V DC
Maximum mechanical load	2,400	N/m ²
Over-current protection	15	A

Electrical data

		NU-E245 (J5)	NU-E240 (J5)	NU-E235 (E2)	
Maximum power	P _{max}	245 W _p	240 W _p	235 W _p	
Open-circuit voltage	V _{OC}	37.5	37.3	37.0	V
Short-circuit current	I _{SC}	8.73	8.63	8.60	A
Voltage at point of maximum power	V _{mpp}	30.5	30.2	30.0	V
Current at point of maximum power	I _{mpp}	8.04	7.95	7.84	A
Module efficiency	η _m	14.9	14.6	14.3	%
NOCT		47.5	47.5	47.5	°C
Temperature coefficient – open-circuit voltage	αV _{OC}	- 130	- 130	- 130	mV / °C
Temperature coefficient – short-circuit current	αI _{SC}	+0.053	+0.053	+0.053	% / °C
Temperature coefficient – power	αP _{max}	- 0.485	- 0.485	- 0.485	% / °C

The electrical data applies under standard test conditions (STCs): irradiation 1,000 W/m² with light spectrum AM 1.5 and a cell temperature of 25 °C. The rated electrical characteristics are subject to a manufacturing tolerance of - 5% / + 10%. NOCT conditions: irradiation of 800 W/m², ambient temperature of 20 °C and wind speed of 1 m/sec.

Characteristic curves NU-E245 (J5)



Applications


- On-grid PV systems
- On-roof PV systems
- Off-grid PV systems
- Ground-mounted PV systems

Please read our detailed installation manual carefully before installing the photovoltaic modules.

Registration

Sharp Solar guarantees safety, product quality and value stability for many years – the only thing we ask is: that you register your modules with the serial numbers so we can send you the warranty certificate. It is quick and easy to register your modules at www.brandaddedvalue.net

Exterior dimensions



Note

Technical data is subject to change without prior notice. Before using Sharp products, please request the latest data sheets from Sharp. Sharp accepts no responsibility for damage to devices which have been equipped with Sharp products on the basis of unverified information.

The specifications may deviate slightly and are not guaranteed. Installation and operating instructions are to be found in the corresponding handbooks, or can be downloaded from www.sharp.eu.

This module should not be directly connected to a load.

Sharp Energy Solution Europe
 a division of Sharp Electronics (Europe) GmbH
 Sonninstrasse 3, 20097 Hamburg, Germany
 Tel: +49 (0) 40 / 23 76 - 0 • Fax: +49 (0) 40 / 23 76 - 21 93
www.sharp.eu

Local responsibility:

Austria
SolarInfo.at@sharp.eu
Benelux
SolarInfo.seb@sharp.eu
Central & Eastern Europe
SolarInfo.scee@sharp.eu

Denmark
SolarInfo.dk@sharp.eu
France
SolarInfo.fr@sharp.eu
Germany
SolarInfo.de@sharp.eu

Scandinavia
SolarInfo.sen@sharp.eu
Spain & Portugal
SolarInfo.es@sharp.eu
Switzerland
SolarInfo.ch@sharp.eu
United Kingdom
SolarInfo.uk@sharp.eu



SolarAccess UK Ltd.

5 Silverdown Office Park, Fair Oak Close, Clyst Honiton • EX5 2UX Exeter
 Tel: +44 (0) 1392 916 000 • Fax: +44 (0) 1392 366 654
www.SolarAccess.co.uk • info@SolarAccess.co.uk